

PROJECT
BIA 702

SISSETON-WAHPETON OYATE
ROBERTS COUNTY, SOUTH DAKOTA
PCAS A0970200 "POW WOW ROAD"
BIA 702 ROADWAY OVERLAY PROJECT
ASPHALT SURFACING, PAVEMENT MARKING, SIGNING


PROJECT LENGTH
4,753.53' (0.900 MILES)

INDEX OF SHEETS

| SECTION | DESCRIPTION |
|-----------|-----------------------------------|
| 1.1 | TITLE SHEET |
| 1.2 | SUMMARY OF ESTIMATE OF QUANTITIES |
| 1.3 - 1.4 | GENERAL NOTES |
| 1.5 - 1.6 | TYPICAL SECTIONS |
| 1.7 | CONCRETE VALLEY GUTTER DETAIL |
| 1.8 - 2.1 | ALIGNMENT GEOMETRY |
| 2.2 | REMOVAL PLAN |
| 2.3 - 2.4 | CONSTRUCTION PLAN |
| 2.5 | SIGN NOTES |
| 2.6 | SIGN TABULATION |
| 2.7 | SIGN PANEL LAYOUT |
| 2.8 - 2.9 | SIGNING STANDARD PLANS |
| 3.0 - 3.5 | LIGHTING PLANS |

LOCATION MAP

PROJECT LOCATION: BIA 702
STA. 100+75.00 TO STA. 148+28.53 (BIA702)



R/W AGREEMENTS

RIGHT-OF-WAY FOR THE ENTIRE PROJECT AS SHOWN ON PLANS HAS BEEN OBTAINED.

UTILITY AGREEMENTS

AGREEMENTS HAVE BEEN COORDINATED WITH UTILITY COMPANIES WHOSE PROPERTIES ARE INVOLVED IN THE RIGHT-OF-WAY AND CONSTRUCTION AREAS FOR THIS PROJECT.

RAILROAD

ALL AGREEMENTS HAVE BEEN OBTAINED FOR ANY RAILROAD CROSSINGS AFFECTED BY THE PROJECT.

SPECIFICATIONS

CONFORM TO SOUTH DAKOTA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES, 2015 EDITION AND REQUIRED PROVISIONS, SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS, OR AS OTHERWISE NOTED IN THESE PLANS.

CERTIFICATION

I CERTIFY THAT THE PS&E MEETS OR EXCEEDS THE DESIGN, HEALTH, AND SAFETY STANDARDS IN APPENDIX B TO SUBPART D OF 25 CFR PART 170.462. I ALSO CERTIFY THAT THE ATTACHED PLANS WERE PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY REGISTERED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF SOUTH DAKOTA.



[Signature]
PROFESSIONAL ENGINEER, P.E.

DATE 12-5-24 REGISTRATION NUMBER 12804

SISSETON-WAHPETON OYATE
TRANSPORTATION PROGRAM


SUBMITTED FOR APPROVAL:


[Signature] 12-6-24
DIRECTOR, SISSETON-WAHPETON OYATE TRIBAL TRANSPORTATION PROGRAM DATE



| | | | | |
|--|-------|---------------|-------------|-----------|
| | STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| | SD | PCAS A0970200 | 1.2 | 3.5 |

| STATEMENT OF ESTIMATED QUANTITIES | | | |
|-----------------------------------|---|----------|--------------------------|
| ITEM NO. | ITEM DESCRIPTION | UNITS | TOTAL ESTIMATED QUANTITY |
| 009E0010 | MOBILIZATION | LUMP SUM | 1 |
| 009E3200 | CONSTRUCTION STAKING | LUMP SUM | 1 |
| 100E0100 | CLEARING | LUMP SUM | 1 |
| 110E1010 | REMOVE ASPHALT CONCRETE PAVEMENT | SQ YD | 352 |
| 110E7150 | REMOVE SIGN FOR RESET | EACH | 3 |
| 210E1005 | SURFACE PREPARATION | MILE | 1 |
| 250E0020 | INCIDENTAL WORK, GRADING | LUMP SUM | 1 |
| 260E1010 | BASE COURSE | TON | 48 |
| 320E1050 | CLASS E ASPHALT CONCRETE | TON | 2633 |
| 330E0010 | MC-70 ASPHALT FOR PRIME | TON | 11 |
| 330E0100 | SS-1H ASPHALT FOR TACK | TON | 7 |
| 632E1320 | 2.0"X2.0" PERFORATED TUBE POST | FT | 270 |
| 632E3205 | FLAT ALUMINUM SIGN, NONREMOVABLE COPY SUPER/VERY HIGH | SQ FT | 268 |
| 633E1222 | HIGH BUILD WATERBORNE PAVEMENT MARKING PAINT, 4" YELLOW | FT | 2468 |
| 633E1230 | HIGH BUILD WATERBORNE PAVEMENT MARKING PAINT, 6" WHITE | FT | 84 |
| 634E0120 | TRAFFIC CONTROL, MISCELLANEOUS | LUMP SUM | 1 |
| 650E6260 | 8" CONCRETE VALLEY GUTTER | SQ YD | 43 |
| 700E0310 | CLASS C RIPRAP | TON | 10 |
| 730E0212 | TYPE G PERMANENT SEED MIXTURE | LB | 31 |
| 732E0250 | FIBER MULCHING | LB | 3580 |
| 734E0150 | 6" DIAMETER EROSION CONTROL WATTLE | FT | 100 |
| 734E5010 | SWEEPING | HOUR | 12 |
| 831E0110 | TYPE B DRAINAGE FABRIC | SQ YD | 10 |



| | | |
|---|---------------------------------------|-----------------|
| BIA 702 OVERLAY SISSETON-WAHPETON OYATE ROBERTS COUNTY, SOUTH DAKOTA | | |
|  | SUMMARY OF ESTIMATE QUANTITIES | |
| | DRAWN BY KJC | CHKD. BY PIA |

| | | | | |
|--|-------|---------------|-------------|-----------|
| | STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| | SD | PCAS A0970200 | 1.3 | 3.5 |

SPECIFICATIONS

Standard Specifications for Roads and Bridges, 2015 Edition and Required Provisions, Supplemental Specifications, and Special Provisions as included in the Proposal.

ENVIRONMENTAL COMMITMENTS

The Sisseton Wahpeton Oyate Tribe (Tribe) is committed to protecting the environment and uses this environmental commitment list as a communication tool for the Engineer and Contractor to ensure that attention is given to avoid, minimize, and/or mitigate an environmental impact.

COMMITMENT 1: WATER SOURCE

The Contractor will not withdraw water with equipment previously used outside the State of South Dakota or previously used in aquatic invasive species waters within South Dakota without prior approval from the Tribe. All construction equipment will be thoroughly washed to prevent and control the introduction and spread of invasive species into the project vicinity.

Action Taken/Required:

The Contractor will obtain the necessary permits from the regulatory agencies, such as the US Army Corps of Engineers (USACE) prior to water extraction activities.

Additional information and mapping of Aquatic Invasive Species in South Dakota can be accessed at: <http://sdleastwanted.com/maps/default.aspx>.

COMMITMENT 2: WATER QUALITY STANDARDS

Action Taken/Required:

The Contractor is advised that the Water Quality Standards, administered by the Environmental Protection Agency (EPA) and USACE, apply to this project. Special construction measures will be taken to ensure the above standard(s) of the surface waters are maintained and protected.

COMMITMENT 3: STORM WATER

Construction activities constitute 1-acre or more of earth disturbance and/or work in a waterway.

Action Taken/Required:

The US Environmental Protection Agency (EPA) 2022 Construction General Permit is required for this project. The Tribe is the owner of this permit and will submit the Notice of Intent (NOI) to EPA 15 days prior to project start in order to obtain coverage. Work can begin after authorization is received from the EPA. This permit provides coverage for construction and dewatering activities for this project.

The Contractor must adhere to the "Special Provision Regarding Storm Water Discharge to Waters of the United States within Indian Reservations."

Storm Water Pollution Prevention Plan

The Storm Water Pollution Prevention Plan (SWPPP) will be developed prior to the submittal of the NOI and will be implemented for all construction activities for compliance with the permit. The SWPPP must be kept on-site and updated as site conditions change. Erosion control measures and best management practices will be implemented in accordance with the SWPPP.

Information on storm water permits and SWPPPs are available on the following websites:

<https://www.epa.gov/npdes/2022-construction-general-permit-cgp>

COMMITMENT 4: TRIBAL MONITORING

Tribal monitors will be required during all earth moving activities. Contact will be made to the SWO prior.

Action Taken/Required:

If evidence of a Tribal Cultural Property (TCP) is identified by Tribal Monitors during project construction activities, such activities will immediately cease and the Project Engineer will be immediately notified. The Project Engineer will work with the THPO to determine the appropriate course of action.

All artifacts, features, or other items of interest uncovered by project construction activities will not be displaced unless the THPO consents to it.

Prior to the pre-construction meeting, the Contractor will notify the THPO to arrange for tribal monitors to be present prior to earth disturbing activities so the tribal monitor is present to monitor the removal of topsoil and identify any cultural resources that may be uncovered during earth disturbing activities.

SEQUENCE OF OPERATIONS

The Contractor will submit a sequence of operations for approval two weeks prior to the preconstruction meeting. If changes to the sequence of operations are proposed during the project, these must be submitted for review a minimum of one week prior to potential implementation. Approval for changes to the sequence of operations will only be allowed when the proposed changes meet with the Engineer's intent for traffic control and sequencing of the work.

Special Conditions

- Asphalt paving along roadway will be completed with a minimum of on - 12 foot lane open to traffic.
- Contractor shall maintain access to driveways during construction.

GENERAL TRAFFIC CONTROL

Existing guide, route, informational logo, regulatory, and warning signs will be temporarily reset and maintained during construction. Removing, relocating, covering, salvaging, and resetting of existing traffic control devices, including delineation, will be the responsibility of the Contractor. Cost for this work will be incidental to the contract unit prices for the various items unless otherwise specified in the plans. Any delineators and signs damaged or lost will be replaced by the Contractor at no cost to the State.

All temporary traffic control sign locations will be set in the field by the Contractor and verified by the Engineer prior to installation.

All construction operations will be conducted in the general direction of traffic movement.

If there is a discrepancy between the traffic control plans, standard plates, and the MUTCD, whichever is more stringent will be used, as determined by the Engineer.

Unless otherwise stated in these plans, work will not be allowed during hours of darkness.

Fixed location signing placed more than 4 calendar days prior to the start of construction will be covered or laid down until the time of construction. The covers must be approved by the Engineer prior to installation. The cost of materials, labor, and equipment necessary to complete this work will be incidental to other contract items. No separate payment will be made.

All fixed location signs, sign posts, and breakaway bases will be removed within 7 calendar days following pavement marking.

TRAFFIC CONTROL, MISCELLANEOUS

Installation, maintenance, relocation and removal of cones, drums, watchmen, tubular markers and flags, construction fence, or any other miscellaneous traffic items shall be included in the lump sum price bid for "Traffic Control, Miscellaneous".

FLAGGING

Operations will be conducted so that the traveling public will not have to wait longer than 15 minutes at the flagger station.

If an emergency vehicle needs to pass through the project, the Contractor will be required to expedite traffic movement. All costs associated with this will be incidental to the contract unit price for "Traffic Control, Miscellaneous".

INCIDENTS

An incident is an emergency road user occurrence, a natural disaster, or other unplanned event that affects or impedes the normal flow of traffic such as a crash, hazardous materials spill, or other event.

The Contractor will set up a meeting prior to start of work to plan and coordinate responses to an incident. The Contractor will invite the South Dakota Highway Patrol, the Sheriff and local emergency response entities to the meeting.

The Contractor will assist to maintain traffic as required by these plan notes and as agreed to at that meeting.

Emergency vehicle access through the project will be considered and discussed at the meeting.

The Contractor should be prepared to relocate advance warning signs if determined to be necessary for a major traffic incident lasting more than two hours. Fixed location ground mounted signs may be covered and additional portable signs provided.

Cost for the relocation of an advance warning sign due to an incident will be 50% of the designated sign rate.

UTILITIES

The Contractor will contact the involved utility companies through South Dakota One Call (1-800-781-7474) prior to starting work. It will be the responsibility of the Contractor to coordinate work with the utility owners to avoid damage to existing facilities.

The Contractor will be aware that the existing utilities shown in the plans were surveyed prior to the design of this project and might have been relocated or replaced by a new utility facility prior to construction of this project, might be relocated or replaced by a new utility facility during the construction of this project, or might not require adjustment and may remain in its current location. The Contractor will contact each utility owner and confirm the status of all existing and new utility facilities. The utility contact information is provided elsewhere in the plans or bidding documents.

CONSTRUCTION STAKING

The Engineer will provide construction staking at the expense of the Owner.

The Contractor will include staking activities in the construction schedule and coordinate work with the Engineer. The Contractor will give 48-hour notification for staking. The Contractor will be responsible for all costs associated with replacing construction stakes which were unnecessarily damaged, destroyed, or removed by the contractor's operations.

MATERIAL WEIGHT TICKETS

The Contractor will clearly identify material stockpiles for various products used on the project, i.e. temporary surfacing, base course, gravel surfacing etc.

The Contractor will submit weight tickets for all items including incidental work items, not just pay items. All weight tickets will be clearly marked.


SAWING OF EXISTING SURFACING

Where new asphalt concrete is placed adjacent to existing asphalt pavement, the existing pavement will be sawed full depth to a true and vertical face. No separate payment will be made for sawing.

GRADING

Surface Preparation shall be applied to the alignments of BIA702 and Access Rd. Bid item shall be paid per mile of roadway. Payment includes the furnishing of all equipment, labor and skill necessary for shaping and compacting the existing roadway surface prior to placing of the asphalt concrete.

Incidental Work, Grading shall be applied to the alignment of Service Rd. Bid item shall be paid per the lump sum. Payment includes the Payment includes the furnishing of all equipment, labor and skill necessary for shaping and compacting the existing subbase prior to the placement of the proposed aggregate base.



| | | |
|---|---------------------------------|-----------------|
| BIA 702 OVERLAY SISSETON-WAHPETON OYATE ROBERTS COUNTY, SOUTH DAKOTA | | |
| | GENERAL NOTES AND TABLES | |
| | DRWN. BY TD | CHKD. BY PIA |

| | | | | |
|--|-------|---------------|-------------|-----------|
| | STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| | SD | PCAS A0970200 | 1.4 | 3.5 |

CLASS E ASPHALT CONCRETE

The asphalt section will be four inches (4") of Class E Asphalt Concrete. Asphalt concrete will be placed in two (2) lifts. The thickness of the top lift will not exceed two inches (2").

Mineral aggregate for Asphalt Concrete Composite will conform to the requirements for Class E.

All other requirements for Class E will apply.

Compaction of asphalt concrete will be by the Specified Roller Coverage Method.

All costs for the asphalt concrete including labor, equipment, and materials will be incidental to the contract unit price per ton for, "Class E Asphalt Concrete".

| STATION TO STATION | ASPHALT CONCRETE COMPOSITE (TONS) |
|---|-----------------------------------|
| BIA 702 STA. 100+75 TO STA. 148+29 | 2,176 TONS |
| SERVICE RD STA. 200+11 TO STA. 204+91 | 160 TONS |
| ACCESS RD STA. 301+16 TO STA. 304+94 | 114 TONS |
| ELDERS ACCESS STA. 400+00 TO STA. 406+27 | 183 TONS |
| TOTAL: | 2,633 TONS |

MISCELLANEOUS CONCRETE

Concrete for curb and gutter, fillets, valley gutters, and sidewalk shall be Class M-6 as detailed in the SDDOT Standards Specifications Section 462.

Concrete shall be cured using a curing compound in accordance with section 821.1 of the SDDOT Standard Specification for Roads and Bridges. A 1/2" preformed expansion material shall be placed between the sidewalk and other concrete items (back of curb, driveways, existing sidewalks, etc.) except at curb ramps, where the expansion material shall be placed on the back side of the landing area. Payment for this item shall be incidental and included in the unit price for the respective bid item.

TABLE OF CONCRETE VALLEY GUTTER

| STATION TO STATION | LT/RT | QUANTITTY (SQ YD) |
|--------------------------------------|---------------|-------------------|
| BIA 702 STA. 122+98 & STA. 130+93 | 8' LT - 8' RT | 43 SQ YD |

HIGH BUILD WATERBORNE PAVEMENT MARKING PAINT

All materials will be applied as per manufacturer's recommendations. High build waterborne pavement marking paint will conform to the supplemental specifications for Section 980.1 B.

Reflective media will consist of glass beads.

High Build Waterborne Pavement Marking Paint applied after October 15 must be formulated as cold-weather waterborne paint. Cold weather waterborne paint will meet the requirements of Section 980.1 C.

RATES OF MATERIALS FOR HIGH BUILD WATERBORNE PAVEMENT MARKING PAINT

Solid 4"line = 22.5 Gal/Mile
Dashed 4"line = 6.2 Gal/Mile
Glass Beads = 8 Lbs/Gal.

All cost for materials, labor and equipment necessary to furnish and install the pavement markings will be incidental to the contract unit price for the respective High Build Waterborne Pavement Marking Paint items.

SHOP DRAWING AND CATALOG CUTS SUBMITTALS

The Contractor will submit shop drawings and catalog cuts in accordance with Section 985 of the Specifications.

Adobe PDF submittals will be sent to the following email address:

Darin.Falcon@KLJeng.com

OML NOTE:

Ensure if any disturbed areas on the project to restore w topsoil and seed, of if other erosion control measures may be needed during construction. We may need to remove, change, or add notes pertaining to EC and restoration below as needed.

PERMANENT SEEDING

The areas to be seeded consist of all newly graded areas within the project limits.

Type G Permanent Seed Mixture will consist of the following:

| GRASS SPECIES | VARIETY | PURE LIVE SEED (PLS) (POUNDS/ACRE) |
|--|---|------------------------------------|
| Western Wheatgrass | Arriba, Flintlock, Rodan, Rosana, Walsh | 7 |
| Switchgrass | Dacotah, Forestburg, Nebraska 28, Pathfinder, Summer, Sunburst, Trailblazer | 3 |
| Indiangrass | Holt, Tomahawk, Chief, Nebraska 54 | 3 |
| Big Bluestream | Bison, Bonilla, Champ, Sunnyview, Roundtree, Bonanza | 3 |
| Oats or Spring Wheat: April through May Winter Wheat: August through November | | 10 |
| TOTAL: | | 26 |

FERTILIZING

Application of fertilizer will not be required on this project.

MYCORRHIZAL INOCULUM

Mycorrhizal inoculum will consist of mycorrhizal fungi spores and mycorrhizal fungi-infected root fragments in a solid carrier. The carrier may include organic materials, calcinated clay, or other materials consistent with application and good plant growth. The supplier will provide certification of the fungal species claimed and the live propagule count. The inoculum will include the following fungal species:

- 25% *Glomus intraradices*
- 25% *Glomus aggregatum or deserticola*
- 25% *Glomus mosseae*
- 25% *Glomus etunicatum*

All seed will be inoculated by the seed supplier with a minimum of 20,000 live propagules of mycorrhizal fungi per 1,000 square feet. All costs of inoculating the seed will be incidental to the contract unit price per pound for the corresponding permanent seed mixture.

The mycorrhizal inoculum will be as shown below or an approved equal:

| PRODUCT | MANUFACTURER |
|----------------------------|--|
| MycoApply | Mycorrhizal Applications, Inc. Grants Pass, OR Phone: 1-866-476-7800 www.mycorrhizae.com |
| AM 120 Multi Species Blend | Reforestation Technologies Int. Gilroy, CA Phone: 1-800-784-4769 www.reforest.com |
| LALRISE Prime and Max WP | Lallemand Specialties Inc. Milwaukee, WI Phone: 1-844-590-7781 www.lallemandplantcare.com |

EROSION CONTROL WATTLE

Erosion control wattles for restraining the flow of runoff and sediment will be installed at locations noted in the table and at locations determined by the Engineer during construction. Refer to Standard Plate 734.06 for details.

The Contractor will provide certification that the erosion control wattles do not contain noxious weed seeds.

Erosion control wattles will remain on the project to decompose.

The erosion control wattle provided will be from the approved product list. The approved product list for erosion control wattle may be viewed at the following internet site:

<http://apps.sd.gov/HC60ApprovedProducts/main.aspx>

FIBER MULCHING

Fiber mulch will be applied in a separate operation following permanent seeding.

Fiber mulch will be applied at the rate of 3,000 pounds per acre.


The Contractor will allow the fiber mulch to cure a minimum of 18 hours prior to watering or any storm event to ensure proper cohesion between the soil and fiber particles.

All costs for the fiber mulch including labor, equipment, and materials will be incidental to the contract unit price per pound for "Fiber Mulching".

The fiber mulch provided will be from the approved product list. The approved product list for fiber mulch may be viewed at the following internet site:

<http://apps.sd.gov/HC60ApprovedProducts/main.aspx>

| STANDARD PLATES | |
|-----------------|--|
| PLATE NO. | DESCRIPTION |
| 632.18 | BREAKAWAY SUPPORT STUB CLEARANCE |
| 632.90 | OFFSETS FOR SIGN INSTALLATION |
| 635.37 | 30' WOOD UTILITY POLE WITH OVERHEAD UTILITY POLE |
| 635.40 | SERVICE CABINET ON OVERHEAD UTILITY POLE |
| 650.40 | VALLEY GUTTER |
| 734.06 | EROSION CONTROL WATTLE |






BIA 702 OVERLAY
SISSETON-WAHPETON OYATE
ROBERTS COUNTY, SOUTH DAKOTA


**GENERAL NOTES
AND TABLES**

| | | |
|----------------|-----------------|---------------------------|
| DRWN: BY TD | CHKD: BY PIA | PROJECT NO. 2311-00858 |
|----------------|-----------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 1.5 | 3.5 |




ROBERTS COUNTY BIA 702 OVERLAY
SISSETON-WAHPETON OYATE
ROBERTS COUNTY, SOUTH DAKOTA



EXISTING TYPICAL SECTIONS

| | | |
|-----------------|-----------------|---------------------------|
| DRAWN BY KJC | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|-----------------|-----------------|---------------------------|


| | | | | |
|--|-------|---------------|-------------|-----------|
| | STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| | SD | PCAS A0970200 | 1.6 | 3.5 |




INSET A




- 4" CLASS E ASPHALT CONCRETE (PLACED IN TWO EVEN 2" LIFTS)
- PLACE SS-1H ASPHALT FOR TACK (APPLY 0.10 GAL/SQYD)
- PLACE MC-70 ASPHALT FOR PRIME (APPLY 0.20 GAL/SQYD)
- 6"-10" EXISTING AGGREGATE



PROPOSED SERVICE RD
STA. 200+00.00 TO STA. 204+91.35 (SERVICE_RD)
STA. 400+00.00 TO STA. 406+27.91 (ELDERS)




INSET B




- 4" CLASS E ASPHALT CONCRETE (PLACED IN TWO EVEN 2" LIFTS)
- PLACE SS-1H ASPHALT FOR TACK (APPLY 0.10 GAL/SQYD)
- PLACE MC-70 ASPHALT FOR PRIME (APPLY 0.20 GAL/SQYD)
- PLACE 8" BASE COURSE

PROPOSED ACCESS RD
STA. 300+00.00 TO STA. 304+94.23 (ACCESS_RD)



ROBERTS COUNTY BIA 702 OVERLAY
SISSETON-WAHPETON OYATE
ROBERTS COUNTY, SOUTH DAKOTA




PROPOSED TYPICAL SECTIONS

| | | |
|-----------------|-----------------|---------------------------|
| DRAWN BY KJC | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|-----------------|-----------------|---------------------------|


| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 1.7 | 3.5 |

CONCRETE VALLEY GUTTER DETAIL

PLAN VIEW




SECTION A-A



GENERAL NOTES:

- PLACE CONCRETE VALLEY GUTTER AT LOW POINTS IN ROADWAY. DRAINAGE TO SURFACE FLOW OVER CONCRETE PAVEMENT.
- PROPOSED VALLEY GUTTER PAID FOR AS 8" CONCRETE VALLEY GUTTER BY THE SQ YD.
- SEE STANDARD PLATE 650.40 FOR ADDITIONAL DETAILS.
- PLACE CLASS C RIPRAP ON DRAINAGE FABRIC AT THE DOWNSTREAM SIDE OF VALLEY GUTTER. RIPRAP TO FOLLOW STANDARD SPEC 700 AND 830. DRAINAGE FABRIC TO FOLLOW STANDARD SPEC 831.
- PLACE EROSION CONTROL WATTLE ON THE UPSTREAM SIDE OF THE VALLEY GUTTER.

PROFILE VIEW






ROBERTS COUNTY BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA



CONCRETE VALLEY
 GUTTER DETAIL

| | | |
|-----------------|-----------------|---------------------------|
| DRAWN BY KJC | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|-----------------|-----------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 1.8 | 3.5 |





BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA

ALIGNMENT PLAN
 BIA 702

| | | |
|-----------------|----------------|---------------------------|
| DRAWN BY KJC | CHKD BY PIA | PROJECT NO. 2311-00858 |
|-----------------|----------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 1.9 | 3.5 |



Curve ACCESS_3
 PI = 304+47.28 Simple Curve
 Delta = 6° 44' 02.03" (RT)
 Da = 3° 16' 26.56"
 R = 1,750.00
 T = 102.96
 L = 205.68

Curve SERVICE_RD_6
 PI = 202+37.17 Simple Curve
 Delta = 18° 58' 12.23" (LT)
 Da = 15° 16' 43.95"
 R = 375.00
 T = 62.65
 L = 124.16

Curve SERVICE_RD_3
 PI = 200+76.94 Simple Curve
 Delta = 10° 02' 16.49" (LT)
 Da = 22° 55' 05.92"
 R = 250.00
 T = 21.36
 L = 43.80


Curve ELDERS_3
 PI = 402+06.18 Simple Curve
 Delta = 24° 39' 14.48" (RT)
 Da = 28° 38' 52.40"
 R = 200.00
 T = 43.71
 L = 86.06

Curve ELDERS_6
 PI = 403+72.04 Simple Curve
 Delta = 25° 22' 02.97" (LT)
 Da = 20° 06' 13.62"
 R = 285.00
 T = 64.14
 L = 126.18

Curve ELDERS_9
 PI = 405+59.73 Simple Curve
 Delta = 6° 51' 03.25" (RT)
 Da = 8° 11' 06.40"
 R = 700.00
 T = 41.90
 L = 83.70



BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA




**ALIGNMENT PLAN
 ELDERS ACCESS**

| | | |
|-----------------|----------------|---------------------------|
| DRAWN BY KJC | CHKD BY PIA | PROJECT NO. 2311-00858 |
|-----------------|----------------|---------------------------|

| | | | | |
|--|-------|---------------|-------------|-----------|
| | STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| | SD | PCAS A0970200 | 2.0 | 3.5 |

| ALIGNMENT TABULATION | | | | | | | | | |
|-------------------------------|-------|-----------|---------------------|----------------|------------|----------|----------|--------------|----------------|
| POINT NUMBER | POINT | STATION | CIRCULAR CURVE DATA | | | | | COORDINATES | |
| | | | DELTA | DEGREE | RADIUS | TANGENT | LENGTH | X | Y |
| | | | SPIRAL CURVE DATA | | | | | | |
| | | | ANGLE (θs) | DEGREE | ST | LT | LS | | |
| BIA 702 <BIA702> | | | | | | | | | |
| 1000 | POT | 100+00.00 | | | | | | 639,012.7815 | 2,721,136.6933 |
| | CC | | | | | | | 635,789.9675 | 2,722,750.6104 |
| 1001 | PC | 106+23.50 | | | | | | 639,191.3182 | 2,721,734.0900 |
| 1002 | PI | 108+83.74 | 8° 23' 07" RT | 1° 36' 50.28" | 3,550.000' | 260.235' | 519.541' | 639,265.8348 | 2,721,983.4282 |
| 1003 | PT | 111+43.05 | | | | | | 639,303.1945 | 2,722,240.9675 |
| | CC | | | | | | | 639,129.6292 | 2,722,716.2523 |
| 1004 | PC | 115+88.49 | | | | | | 639,367.1431 | 2,722,681.7976 |
| 1005 | PI | 116+80.80 | 42° 04' 27" RT | 23° 52' 23.67" | 240.000' | 92.306' | 176.240' | 639,380.3947 | 2,722,773.1472 |
| 1006 | PT | 117+64.73 | | | | | | 639,329.0183 | 2,722,849.8337 |
| | CC | | | | | | | 639,579.5699 | 2,723,131.6300 |
| 1007 | PC | 118+59.39 | | | | | | 639,276.3323 | 2,722,928.4749 |
| 1008 | PI | 119+38.47 | 24° 27' 01" LT | 15° 41' 50.91" | 365.000' | 79.083' | 155.759' | 639,232.3154 | 2,722,994.1763 |
| 1009 | PCC | 120+15.15 | | | | | | 639,219.4399 | 2,723,072.2044 |
| | CC | | | | | | | 639,786.7679 | 2,723,165.8201 |
| | PCC | 120+15.15 | | | | | | 639,219.4399 | 2,723,072.2044 |
| 1010 | PI | 121+54.31 | 27° 12' 39" LT | 9° 57' 52.14" | 575.000' | 139.164' | 273.078' | 639,196.7826 | 2,723,209.5120 |
| 1011 | PT | 122+88.23 | | | | | | 639,239.4187 | 2,723,341.9843 |
| | CC | | | | | | | 639,368.5307 | 2,723,482.0202 |
| 1012 | PC | 124+61.08 | | | | | | 639,292.3777 | 2,723,506.5300 |
| 1013 | PI | 125+30.91 | 82° 13' 52" LT | 71° 37' 11.01" | 80.000' | 69.827' | 114.816' | 639,313.7707 | 2,723,572.9989 |
| 1014 | PT | 125+75.90 | | | | | | 639,382.5214 | 2,723,560.7874 |
| | CC | | | | | | | 639,282.2873 | 2,722,649.2694 |
| 1015 | PC | 126+36.62 | | | | | | 639,442.3060 | 2,723,550.1684 |
| 1016 | PI | 128+00.88 | 20° 21' 16" LT | 6° 15' 42.60" | 915.000' | 164.258' | 325.054' | 639,604.0326 | 2,723,521.4423 |
| 1017 | PCC | 129+61.67 | | | | | | 639,745.6693 | 2,723,438.2574 |
| | CC | | | | | | | 639,695.0265 | 2,723,352.0292 |
| | PCC | 129+61.67 | | | | | | 639,745.6693 | 2,723,438.2574 |
| 1018 | PI | 130+32.77 | 70° 49' 34" LT | 57° 17' 44.81" | 100.000' | 71.101' | 123.615' | 639,806.9781 | 2,723,402.2500 |
| 1019 | PT | 130+85.29 | | | | | | 639,793.1042 | 2,723,332.5161 |
| | CC | | | | | | | 641,157.0629 | 2,722,500.9683 |
| 1020 | PC | 136+34.70 | | | | | | 639,685.8970 | 2,722,793.6639 |
| 1021 | PI | 136+50.12 | 1° 10' 39" RT | 3° 49' 10.99" | 1,500.000' | 15.415' | 30.829' | 639,682.8890 | 2,722,778.5451 |
| 1022 | PT | 136+65.53 | | | | | | 639,680.1924 | 2,722,763.3676 |
| | CC | | | | | | | 639,213.7404 | 2,722,653.2713 |
| 1023 | PC | 138+55.53 | | | | | | 639,646.9557 | 2,722,576.3008 |
| 1024 | PI | 139+76.45 | 30° 44' 04" LT | 13° 01' 18.37" | 440.000' | 120.926' | 236.025' | 639,625.8018 | 2,722,457.2394 |
| 1025 | PT | 140+91.55 | | | | | | 639,546.7714 | 2,722,365.7119 |
| | CC | | | | | | | 639,865.8151 | 2,721,755.9298 |
| 1026 | PC | 143+44.58 | | | | | | 639,381.4064 | 2,722,174.1979 |
| 1027 | PI | 144+81.61 | 24° 10' 13" RT | 8° 57' 08.88" | 640.000' | 137.030' | 269.983' | 639,291.8515 | 2,722,070.4817 |
| 1028 | PT | 146+14.56 | | | | | | 639,252.6139 | 2,721,939.1898 |
| 1029 | POT | 148+28.63 | | | | | | 639,191.3182 | 2,721,734.0900 |




| | | |
|---|--|--------------------------------|
| BIA 702 OVERLAY SISSETON-WAHPETON OYATE ROBERTS COUNTY, SOUTH DAKOTA | | |
| | ALIGNMENT TABULATION BIA 702 | |
| | <small>DRAWN BY</small> KJC | <small>CHKD. BY</small> PIA |

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 2.1 | 3.5 |


| ALIGNMENT TABULATION | | | | | | | | | |
|-------------------------|-------|-----------|---------------------|----------------|---------|----------|----------|--------------|----------------|
| POINT NUMBER | POINT | STATION | CIRCULAR CURVE DATA | | | | | COORDINATES | |
| | | | DELTA | DEGREE | RADIUS | TANGENT | LENGTH | | |
| | | | SPIRAL CURVE DATA | | | | | X | Y |
| | | | ANGLE (θs) | DEGREE | ST | LT | LS | | |
| SERVICE RD <SERVICE_RD> | | | | | | | | | |
| 2000 | POT | 200+00.00 | | | | | | 639,251.7060 | 2,723,380.1613 |
| | CC | | | | | | | 639,406.6591 | 2,723,176.4136 |
| 2001 | PC | 200+54.99 | | | | | | 639,301.6025 | 2,723,403.2684 |
| 2002 | PI | 200+76.94 | 10° 02' 16" LT | 22° 55' 05.92" | 21.956' | 43.799' | 250.000' | 639,321.5253 | 2,723,412.4947 |
| 2003 | PT | 200+98.79 | | | | | | 639,342.7513 | 2,723,418.1072 |
| | CC | | | | | | | 639,511.8258 | 2,723,074.9255 |
| 2004 | PC | 201+74.51 | | | | | | 639,415.9641 | 2,723,437.4659 |
| 2005 | PI | 202+37.17 | 18° 58' 12" LT | 15° 16' 43.95" | 62.653' | 124.159' | 375.000' | 639,476.5352 | 2,723,453.4819 |
| 2006 | PT | 202+98.67 | | | | | | 639,539.0230 | 2,723,448.9379 |
| 2007 | POT | 204+91.35 | | | | | | 639,731.1900 | 2,723,434.9640 |

| ALIGNMENT TABULATION | | | | | | | | | |
|-----------------------|-------|-----------|---------------------|---------------|----------|----------|------------|--------------|----------------|
| POINT NUMBER | POINT | STATION | CIRCULAR CURVE DATA | | | | | COORDINATES | |
| | | | DELTA | DEGREE | RADIUS | TANGENT | LENGTH | | |
| | | | SPIRAL CURVE DATA | | | | | X | Y |
| | | | ANGLE (θs) | DEGREE | ST | LT | LS | | |
| ACCESS RD <ACCESS_RD> | | | | | | | | | |
| 3000 | POT | 300+00.00 | | | | | | 639,793.1042 | 2,723,332.5161 |
| | CC | | | | | | | 638,143.9322 | 2,724,011.7002 |
| 3001 | PC | 303+44.32 | | | | | | 639,860.2925 | 2,723,670.2220 |
| 3002 | PI | 304+47.28 | 6° 44' 02" RT | 3° 16' 26.56" | 102.956' | 205.675' | 1,750.000' | 639,880.3823 | 2,723,771.1991 |
| 3003 | PT | 305+50.00 | | | | | | 639,888.4932 | 2,723,873.8352 |

| ALIGNMENT TABULATION | | | | | | | | | |
|------------------------|-------|-----------|---------------------|----------------|---------|----------|----------|--------------|----------------|
| POINT NUMBER | POINT | STATION | CIRCULAR CURVE DATA | | | | | COORDINATES | |
| | | | DELTA | DEGREE | RADIUS | TANGENT | LENGTH | | |
| | | | SPIRAL CURVE DATA | | | | | X | Y |
| | | | ANGLE (θs) | DEGREE | ST | LT | LS | | |
| ELDERS ACCESS <ELDERS> | | | | | | | | | |
| 4000 | POT | 400+00.00 | | | | | | 639,385.4235 | 2,722,809.2116 |
| | CC | | | | | | | 639,206.6082 | 2,722,994.7481 |
| 4001 | PC | 401+62.48 | | | | | | 639,405.1314 | 2,722,970.4887 |
| 4002 | PI | 402+06.18 | 24° 39' 14" RT | 28° 38' 52.40" | 43.706' | 86.059' | 200.000' | 639,410.4328 | 2,723,013.8718 |
| 4003 | PT | 402+48.54 | | | | | | 639,397.1542 | 2,723,055.5117 |
| | CC | | | | | | | 639,650.6468 | 2,723,198.6565 |
| 4004 | PC | 403+07.90 | | | | | | 639,379.1187 | 2,723,112.0684 |
| 4005 | PI | 403+72.04 | 25° 22' 03" LT | 20° 06' 13.62" | 64.143' | 126.183' | 285.000' | 639,359.6310 | 2,723,173.1789 |
| 4006 | PT | 404+34.08 | | | | | | 639,368.2035 | 2,723,236.7461 |
| | CC | | | | | | | 638,685.6765 | 2,723,413.3000 |
| 4007 | PC | 405+17.83 | | | | | | 639,379.3968 | 2,723,319.7467 |
| 4008 | PI | 405+59.73 | 6° 51' 03" RT | 8° 11' 06.40" | 41.900' | 83.700' | 700.000' | 639,384.9966 | 2,723,361.2705 |
| 4009 | PT | 406+01.53 | | | | | | 639,385.6032 | 2,723,403.1658 |
| 4010 | POT | 406+27.91 | | | | | | 639,385.9850 | 2,723,429.5389 |





BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA




ALIGNMENT TABULATION
 SERVICE RD, ELDERS
 ACCESS & ACCESS RD



| | | |
|-----------------|-----------------|---------------------------|
| DRWN: BY KJC | CHKD: BY PIA | PROJECT NO. 2311-00858 |
|-----------------|-----------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 2.2 | 3.5 |



| | |
|---|---|
| BIA 702 OVERLAY SISSETON-WAHPETON OYATE ROBERTS COUNTY, SOUTH DAKOTA | |
|  | REMOVAL PLAN STA. 100+75 TO STA. 114+30 |
| <small>DRAWN BY</small> KJC | <small>CHKD. BY</small> PIA |
| <small>PROJECT NO.</small> 2311-00858 | |

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 2.3 | 3.5 |






BIA 702 OVERLAY
 Sisseton-Wahpeton OYATE
 ROBERTS COUNTY, SOUTH DAKOTA

KLJ

CONSTRUCTION PLAN
 STA. 100+75 TO STA. 114+30

| | | |
|-----------------|-------------------|---------------------------|
| DRAWN BY KJC | CHECKED BY PIA | PROJECT NO. 2311-00858 |
|-----------------|-------------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 2.4 | 3.5 |



BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA

KLJ

CONSTRUCTION PLAN
 STA. 114+30 TO STA. 139+50

| | | |
|-----------------|-------------------|---------------------------|
| DRAWN BY KJC | CHECKED BY PIA | PROJECT NO. 2311-00858 |
|-----------------|-------------------|---------------------------|

SECTION S – ESTIMATE OF QUANTITIES – BIA 702 OVERLAY

| ITEM NO. | Item | Quantity | Unit |
|----------|--|----------|------|
| 632E1320 | 2.0"x2.0" Perforated Tube Post | 270 | Ft |
| 632E3205 | Flat Aluminum Sign, Non removable Copy Super/Very High Intensity | 267.6 | SqFt |

GENERAL PERMANENT SIGNING

New sign installations will be staked in the field by the Contractor and checked by the Engineer. The Contractor will give the Engineer a minimum of one week to check staked locations prior to signpost installation. Lateral offset of signs will be as shown in the plans or as directed by the Engineer.

The Contractor will be responsible for contacting South Dakota One Call to locate the utilities at the staked sign installation locations.

When signs are mounted in an assembly, they will be 1-2 inches apart vertically and horizontally.

The height of the post must not exceed the minimum height needed by more than 0.5 feet. Any portion that extends above the sign will be cut off. No separate payment will be made for cutting the post or for that length cut off.

Aluminum U-Channel stiffeners will be used on all signs 36 inches or greater in width and will conform to ASTM B221 Alloy 6063-T6 or 6061-T6. The U-Channel will be 2 inches in width and free of holes. The U-Channel stiffeners will also be used to connect various signs together so that an entire sign assembly can be erected on a single installation. Stiffeners may be fastened to signs by use of 1/4-inch diameter drive rivets.

The Contractor will use 3/8-inch diameter rust proof machine sign bolts, flat metal washers, neoprene washers (against the sign sheeting), lock washers, and nuts to fasten the sign to the channel aluminum and posts. A minimum of two bolts will extend through each post.

Prior to ordering signs, the Contractor will verify dimensions, background, border, and legend of the signs.

Prior to use, the Contractor will provide documentation for the sign support devices showing they meet the applicable NCHRP 350 or MASH requirements.

REMOVE TRAFFIC SIGN

Existing signs that are shown as being removed in the Permanent Signing Table will become the property of the Contractor. Existing signposts and bases will be removed in their entirety. All existing signs, posts, and/or hardware removed will not be reused. Holes remaining from the removal of wood posts will be backfilled and compacted with material placed in layers not to exceed 6 inches in depth.

All costs associated with the removal of existing signs, posts, hardware, and backfilled holes will be incidental to the contract unit price per each for "Remove Traffic Sign". Quantities will be per assembly at the contract unit price per each.

NEW PERMANENT SIGNING

All signs will be manufactured in accordance with the sheeting manufacturer's recommendations utilizing a matched component system, including inks, electronic cuttable films, and protective overlay films.

All Flat Aluminum Signs, Nonremovable Copy High Intensity will have sheeting in conformance with the requirements of ASTM D4956 Type IV. All Flat Aluminum Signs, Nonremovable Copy Super/Very High Intensity will have sheeting in conformance with the requirements of ASTM D4956 Type XI.

All costs associated with furnishing and installing the new permanent signs, and with furnishing and installing stiffeners and hardware will be incidental to the contract unit price per square foot for "Flat Aluminum Sign, Nonremovable Copy Super/Very High Intensity".

DIGITALLY PRINTED SIGNS

Digitally printed signs will be allowed on this project. If the Contractor elects to provide digitally printed signs, such signs will adhere to the following specifications.

PROTECTIVE OVERLAY FILM

Permanent traffic signs printed with digital ink systems will be fabricated with a full sign protective overlay film designed to provide a smooth surface needed for retroreflectivity, and to protect the sign from fading and UV degradation. The overlaminates will comply with the retroreflective sheeting manufacturer's recommendations to ensure proper adhesion and transparency and will also meet the reflective film durability as identified in Table 1.

Table 1: Retroreflective Film Minimum Durability Requirements

| ASTM D4956 Type | Full Sign Replacement Term (years) | Sheeting Replacement Term (years) |
|-----------------|------------------------------------|-----------------------------------|
| I | 0 | 7 |
| III | 7 | 10 |
| IV | 7 | 10 |
| VIII | 7 | 10 |
| IX | 7 | 12 |
| XI | 7 | 12 |

FABRICATION

Retroreflective sheeting will be applied to a properly cleaned and prepared aluminum sign blank in accordance with the retroreflective sheeting manufacturer's recommendations. Sign legend will be applied using digital print technologies and systems in accordance with the retroreflective sheeting manufacturer's recommendations and the requirements of these plans.

Finished signs will be free of ragged edges and must be supplied clean and free of scratches, grease, oil, lubricants or other contaminants. Minor blemishes (dirt speck, dust, etc.) may settle on the fresh ink surface or become entrapped between the sheeting surface and transparent overlay film due to static charge within the sign shop environment. Any blemish must be minor and not interfere with the communication of the sign message to the motorist. The blemish must not be visible to the naked eye when viewed from 30 feet or greater.

| | | | |
|-----------------------|---------------|-------|--------------|
| STATE OF SOUTH DAKOTA | PROJECT | SHEET | TOTAL SHEETS |
| | PCAS A0970200 | 2.5 | 3.5 |

After application of the retroreflective sheeting, sign blanks will be stacked and packaged face to face, back to back, and protected in accordance with the sheeting manufacturer's recommendations. Finished signs will be securely packaged to prevent damage during transit or storage according to the sheeting manufacturer's recommendations.

TRAFFIC SIGN PERFORMANCE WARRANTY PROVISIONS

Based on the ASTM Type of sheeting specified, traffic control signs will be warranted for the duration shown in Table 1. Full product terms and conditions are as established by each sheeting manufacturer and may contain certain limitations based on sheeting and ink colors, and geographic exposure of the sign. A copy of the warranty document with complete details of terms and conditions will be supplied if requested by the Engineer.


CERTIFIED DIGITAL SIGN FABRICATOR

Sign fabricators using digital imaging methods to produce regulated traffic signs must be certified by the reflective sheeting manufacturer whose materials are used to produce the delivered signs.

DATE TAGGING SIGNS WITH PERTINENT INFORMATION

All digitally printed signs are required to be date-tagged with the following 2 components:

- Date tags on the back of signs
Tags will have the following information and be fabricated with material and printing system that are as durable as the warranted sign.
 - Name of Sign Fabricator
 - Date the sign was fabricated (month and year)
 - Process that was used for sign fabrication (digitally printed)
 - Supplier of sheeting that was used for fabricating the sign.
- Border date
The month and year (mm/yyyy) of sign fabrication will be printed in the border of the sign in 3/8" sans serif font. Border date will be printed with the same warranted printed system as the sign face. The date should be printed in the locations indicated below.




SQUARE TUBE ANCHOR SLEEVE

The Contractor will furnish and install new 2.5" x 2.5" x 18", 12 Gauge square tube anchor sleeve or equivalent components as approved by the Engineer for 2.0" x 2.0" perforated tube posts. A 2.25" x 2.25" x 4', 12 Gauge perforated tube post will be used as the anchor post for installation with the square tube anchor sleeve.

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 2.6 | 3.5 |

| Description | SIGN | | | | POST | | | | | | | Remarks | | |
|--|------------|-------------|-----------------|----------------------|----------------------------|------------------------------|-------------------|-------------------------------|--|--------------------------|--|---------|---|------------------------------|
| | Width (In) | Height (In) | Sign Code | Direction Sign Faces | Remove Traffic Sign (Each) | Remove Sign for Reset (Each) | Reset Sign (Each) | Type IV High Intensity (SqFt) | Type XI Super/Very High Intensity (SqFt) | Flourescent Yellow/Green | 2.0"X2.0" Perforated Tube Post 12 ga. (FT) | | (N.A.B.I.) Square Tube Anchor Sleeve (Each) | Current Type of Post |
| SPEED LIMIT 10 | 24 | 30 | R2-1 | W | | | | | 5.0 | | | | | |
| Maka Iyutapi Wikcemna Hehanyan Omani Pi/P | 42 | 30 | SPECIAL SIGN 1 | W | | | | | 8.8 | | 16.0 | 1 | | Install New Sign on New Post |
| COME BACK SOON Ecaḡna hdi pi/po | 96 | 24 | SPECIAL SIGN 7 | E | | | | | 16.0 | | 13.0 | 2 | | Install New Sign on New Post |
| WELCOME Tanyan yahipi | 54 | 24 | SPECIAL SIGN 9 | W | | | | | 9.0 | | 13.0 | 2 | | Install New Sign on New Post |
| CHILDREN AT PLAY | 36 | 36 | SPECIAL SIGN 4 | W | | | | | 9.0 | | 16.0 | 1 | | Install New Sign on New Post |
| Wakta uḡ pi/po ; Šiceca Škatapi | 36 | 36 | SPECIAL SIGN 5 | W | | | | | 9.0 | | 16.0 | 1 | | Install New Sign on New Post |
| DO NOT ENTER | 30 | 30 | R5-1 | W | | | | | 6.3 | | | | | |
| Hiyu šni pi/po | 30 | 30 | SPECIAL SIGN 8 | W | | | | | 6.3 | | 13.0 | 1 | | Install New Sign on New Post |
| END ONE WAY | 24 | 30 | R6-7 | E | | | | | 5.0 | | | | | |
| Ocaḡku deciyotaḡhaḡ iḡaḡke | 36 | 24 | SPECIAL SIGN 13 | E | | | | | 6.0 | | | | | |
| YIELD | 30 | 30 | R1-2 | E | | | | | 6.3 | | | | | |
| H'aḡhiya u | 30 | 30 | SPECIAL SIGN 10 | E | | | | | 6.3 | | 16.0 | 1 | | Install New Sign on New Post |
| SPEED LIMIT 10 | 24 | 30 | R2-1 | W | | | | | 5.0 | | | | | |
| Maka Iyutapi Wikcemna Hehanyan Omani Pi/P | 42 | 30 | SPECIAL SIGN 1 | W | | | | | 8.8 | | 16.0 | 1 | | Install New Sign on New Post |
| BEGIN ONE WAY | 24 | 30 | R6-6 | W | | | | | 5.0 | | 13.5 | 1 | | Install New Sign on New Post |
| Elders Handicapped Pow Wow Staff ONLY | 66 | 48 | SPECIAL SIGN 11 | W | | | | | 22.0 | | 16.0 | 1 | | Install New Sign on New Post |
| Wicaḡcana, winuḡcana, ga tuwe ḡtanipi eceena | 42 | 36 | SPECIAL SIGN 12 | W | | | | | 10.5 | | | | | |
| TRAILER SITE | 24 | 24 | RS-040 | W | | | | | 4.0 | | | | | |
| RIGHT ARROW | 21 | 15 | M6-1P | W | | | | | 2.2 | | 14.5 | 1 | | Install New Sign on New Post |
| CAMPER ACCESS | 78 | 30 | SPECIAL SIGN 6 | N | | | | | 16.3 | | 13.5 | 1 | | Install New Sign on New Post |
| BUMP AHEAD | 36 | 36 | SPECIAL SIGN 2 | W | | | | | 9.0 | | | | | |
| Wakta uḡ , caḡku škopa | 36 | 36 | SPECIAL SIGN 3 | W | | | | | 9.0 | | 16.0 | 1 | | Install New Sign on New Post |
| SPEED LIMIT 10 | 24 | 30 | R2-1 | E | | | | | 5.0 | | | | | |
| Maka Iyutapi Wikcemna Hehanyan Omani Pi/P | 42 | 30 | SPECIAL SIGN 1 | E | | | | | 8.8 | | 16.0 | 1 | | Install New Sign on New Post |
| BUMP AHEAD | 36 | 36 | SPECIAL SIGN 2 | E | | | | | 9.0 | | | | | |
| Wakta uḡ , caḡku škopa | 36 | 36 | SPECIAL SIGN 3 | E | | | | | 9.0 | | 16.0 | 1 | | Install New Sign on New Post |
| YIELD | 30 | 30 | R1-2 | E | | | | | 6.3 | | | | | |
| H'aḡhiya u | 30 | 30 | SPECIAL SIGN 10 | E | | | | | 6.3 | | 16.0 | 1 | | Install New Sign on New Post |
| YIELD | 30 | 30 | R1-2 | S | | | | | 6.3 | | | | | |
| H'aḡhiya u | 30 | 30 | SPECIAL SIGN 10 | S | | | | | 6.3 | | 16.0 | 1 | | Install New Sign on New Post |
| TRAILER SITE | 24 | 24 | RS-040 | S | | | | | 4.0 | | | | | |
| CAMPING | 24 | 24 | D9-3 | S | | | | | 4.0 | | 16.0 | 1 | | Install New Sign on New Post |
| RIGHT ARROW | 21 | 15 | M6-1P | S | | | | | 2.2 | | | | | |
| CAMPER ACCESS | 78 | 30 | SPECIAL SIGN 6 | N | | | | | 16.3 | | 13.5 | 2 | | Install New Sign on New Post |
| | | | | | Total | 0 | 0 | 0 | 0.0 | 267.6 | 270.0 | 21 | | |




BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA

KLJ


SIGN TABULATION

DRAWN BY: KJC CHECKED BY: PIA PROJECT NO.: 2311-00858


| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 2.7 | 3.5 |



1.50" Radius, 0.63" Border, 0.38" Indent, Black on White:
"SPEED", E 2K;
"LIMIT", E 2K; "10", E 2K;



1.88" Radius, 0.75" Border, 0.50" Indent, Black on White:
"Maka lyutapi", Arial; "Wikcemna", Arial;
"Heharyan", Arial; "Omani Pi/Po", Arial



36.00" across sides 0.88" Border, 0.63" Indent, Black on Yellow:
"BUMP", C 2K; "AHEAD", C 2K 25% spacing;




36.00" across sides 0.88" Border, 0.63" Indent, Black on Yellow:
"Wakta un", Arial 70% spacing;
"canku škopa", Arial 3% spacing




36.00" across sides 0.88" Border, 0.63" Indent, Black on Yellow:
"CHILDREN", C 2K; "AT PLAY", C 2K 80% spacing;




36.00" across sides 0.88" Border, 0.63" Indent, Black on Yellow:
"Wakta un pi/po", Arial 70% spacing;
"Šiceca Škatapi", Arial 70% spacing




3.00" Radius, 1.00" Border, White on Green:
"CAMPER ACCESS", D 2K; "Wakeya itoksu onaziŋpi", Arial




3.00" Radius, 1.00" Border, White on Brown:
"COME BACK SOON", E Mod 2K; "Ecaŋna hdi pi/po", Arial




1.88" Radius, No border, White:




1.88" Radius, No border, Black on White:
Rounded Rectangle 14.50" Radius Red:




3.00" Radius, 1.00" Border, White on Brown:
"WELCOME", E Mod 2K; "Tanyan yahipi", Arial




36.00" corner to corner 2.00" Radius, 5.00" Border, 0.75" Indent, Red on White:
"YIELD", C 2K specified length:




36.00" corner to corner 2.00" Radius, 5.00" Border, 0.75" Indent, Red on White:
"Hanyia u", Arial specified length




1.50" Radius, 0.63" Border, 0.38" Indent, Black on White:
"Elders", D 2K; "Handicapped", D 2K; "Pow Wow Staff", D 2K 59% spacing;
"ONLY", D 2K;




1.50" Radius, 0.63" Border, 0.38" Indent, Black on White:
"Wicaŋcana", Arial; "winuŋcana", Arial
"ga tuwe htanipi", Arial; "eceena upi", Arial



1.50" Radius, 0.63" Border, 0.38" Indent, Black on White:
"END", D 2K specified length;
"ONE", D 2K specified length;
"WAY", D 2K specified length;



1.50" Radius, 0.63" Border, 0.38" Indent, Black on White:
"Ocaŋku", Arial;
"deciyotanhan", Arial 60% spacing;
"ihanke", Arial;





BIA 702 OVERLAY
SISSETON-WAHPETON OYATE
ROBERTS COUNTY, SOUTH DAKOTA


SIGN PANEL LAYOUTS

DRAWN BY: KJC
CHKD BY: PIA
PROJECT NO.: 2311-00858

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 2.8 | 3.5 |



| | | |
|---|--------------------------------|--------------------------------|
| BIA 702 OVERLAY SISSETON-WAHPETON OYATE ROBERTS COUNTY, SOUTH DAKOTA | | |
| | STANDARD PLATES | |
| | <small>DRAWN BY</small> KJC | <small>CHKD. BY</small> PIA |



TWO POST BREAKAWAY SIGN SUPPORTS


GENERAL NOTES:

The number of stiffeners used (N) will be as follows:
 If $H \leq 2'-0"$ then $N = 1$
 If $2'-0" < H \leq 8'-0"$ then $N = 2$
 If $8'-0" < H \leq 15'-0"$ then $N = 3$
 where H is the vertical dimension of the sign.

A minimum of two bolts will be required to fasten the sign to each post.

November 19, 2020

| | | | |
|----------------------|-----------------------|------------------------|--------------|
| Published Date: 2025 | S D D O T | SIGN STIFFENER DETAILS | PLATE NUMBER |
| | | | 632.60 |
| | | | Sheet 2 of 2 |



ROADSIDE SIGN IN BUSINESS, COMMERCIAL, OR RESIDENTIAL AREA

WARNING SIGN ADVISORY SPEED PLAQUE IN RURAL AREA

ROADSIDE SIGN IN RURAL AREA

SIGN ON NOSE OF MEDIAN

* Where parking or pedestrian movements are likely to occur.

November 19, 2020

| | | | |
|----------------------|-----------------------|-------------------------------|--------------|
| Published Date: 2025 | S D D O T | OFFSETS FOR SIGN INSTALLATION | PLATE NUMBER |
| | | | 632.90 |
| | | | Sheet 1 of 1 |

BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA


STANDARD PLATES


| | | |
|-----------------|-----------------|---------------------------|
| DRWN. BY KJC | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|-----------------|-----------------|---------------------------|

| | | | | |
|--|-------|---------------|-------------|-----------|
| | STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| | SD | PCAS A0970200 | 3.0 | 3.5 |

| STATEMENT OF ESTIMATED QUANTITIES | | | |
|-----------------------------------|--|-------|--------------------------|
| ITEM NO. | ITEM DESCRIPTION | UNITS | TOTAL ESTIMATED QUANTITY |
| 635E0040 | BREAKAWAY BASE LUMINAIRE POLE WITH ARM, 40' MOUNTING | EACH | 13 |
| 635E3700 | ROADWAY LUMINAIRE, POLE PHOTOELECTRIC CELL | EACH | 16 |
| 635E5020 | 2' DIAMETER FOOTING | FT | 26 |
| 635E5301 | TYPE 1 ELECTRICAL JUNCTION BOX | EACH | 4 |
| 635E5400 | ELECTRICAL SERVICE CABINET | EACH | 3 |
| 635E9016 | 1/C #6 AWG COPPER WIRE (1-2) | FT | 3671 |

| ALTERNATE A - AREA LIGHTING, NON-TTP FUNDING SOURCE | | | |
|---|--|------|----|
| 635E3700 | ROADWAY LUMINAIRE, POLE PHOTOELECTRIC CELL | EACH | 10 |
| | | | |
| | | | |






| | | |
|---|----------------------------|-----------------|
| BIA 702 OVERLAY SISSETON-WAHPETON OYATE ROBERTS COUNTY, SOUTH DAKOTA | | |
|  | LIGHTING QUANTITIES | |
| | DRAWN BY TD | CHKD. BY PIA |

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 3.1 | 3.5 |


LEGEND

| EXISTING | PROPOSED | |
|----------|----------|---|
| | | UTILITY ELECTRICAL LINE |
| | | SISSETON WAHPETON OYATE ELECTRICAL LINE |
| | | TRANSFORMER |
| | | WOOD POLE |
| | | DISCONNECT SWITCH |
| | | POLE AND ROADWAY LED |
| | | AREA LIGHT ON EXISTING POLE (ALTERNATE A) |




| | | | | | | |
|---|---|-------------|----------|-------------|----|-----|
| BIA 702 OVERLAY SISSETON-WAHPETON OYATE ROBERTS COUNTY, SOUTH DAKOTA | | | | | | |
| | LIGHTING LAYOUT STA. 100+75 TO STA. 114+30 | | | | | |
| | <table border="1"> <tr> <td>DRAWN BY</td> <td>CHKD. BY</td> <td>PROJECT NO.</td> </tr> <tr> <td>TD</td> <td>PIA</td> <td>2311-00858</td> </tr> </table> | DRAWN BY | CHKD. BY | PROJECT NO. | TD | PIA |
| DRAWN BY | CHKD. BY | PROJECT NO. | | | | |
| TD | PIA | 2311-00858 | | | | |

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 3.2 | 3.5 |



LEGEND

| EXISTING | PROPOSED | |
|----------|----------|---|
| | | UTILITY ELECTRICAL LINE |
| | | SISSETON WAHPETON OYATE ELECTRICAL LINE |
| | | TRANSFORMER |
| | | WOOD POLE |
| | | DISCONNECT SWITCH |
| | | POLE AND ROADWAY LED |
| | | AREA LIGHT ON EXISTING POLE (ALTERNATE A) |




BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA

KLJ

LIGHTING LAYOUT ALTERNATE
 STA. 114+30 TO STA. 139+50



| | | |
|----------------|-----------------|---------------------------|
| DRWN. BY TD | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|----------------|-----------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 3.3 | 3.5 |



LEGEND

| EXISTING | PROPOSED | |
|----------|----------|---|
| | | UTILITY ELECTRICAL LINE |
| | | SISSETON WAHPETON OYATE ELECTRICAL LINE |
| | | TRANSFORMER |
| | | WOOD POLE |
| | | DISCONNECT SWITCH |
| | | POLE AND ROADWAY LED |
| | | AREA LIGHT ON EXISTING POLE (ALTERNATE A) |




BIA 702 OVERLAY
 SISSETON-WAHPETON OYATE
 ROBERTS COUNTY, SOUTH DAKOTA

KLJ

LIGHTING LAYOUT ALTERNATE
 STA. 114+30 TO STA. 139+50

| | | |
|----------------|-----------------|---------------------------|
| DRWN. BY TD | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|----------------|-----------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 3.4 | 3.5 |



LEGEND:
 FUSE: 6 amp. Non-Time Delay
or
2 8/10 amp. Dual Element
 LUMINAIRE: LED
 GROUND ROD

NOTE:
All circuits will be bonded in accordance with the NATIONAL ELECTRICAL CODE. Quantities for bonding conductors are not included in these plans.






BIA 702 OVERLAY
SISSETON-WAHPETON OYATE
ROBERTS COUNTY, SOUTH DAKOTA


LIGHTING DETAILS

| | | |
|----------------|-----------------|---------------------------|
| DRWN. BY TD | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|----------------|-----------------|---------------------------|

| | | | |
|-------|---------------|-------------|-----------|
| STATE | PROJECT NO. | SECTION NO. | SHEET NO. |
| SD | PCAS A0970200 | 3.5 | 3.5 |



BIA 702 OVERLAY
SISSETON-WAHPETON OYATE
ROBERTS COUNTY, SOUTH DAKOTA



STANDARD PLATES

| | | |
|----------------|-----------------|---------------------------|
| DRWN. BY TD | CHKD. BY PIA | PROJECT NO. 2311-00858 |
|----------------|-----------------|---------------------------|